

Sampling and Testing Guide-Minimum Frequency

Matls. IM 204
Appendix K (Metric) Units

COLD-IN-PLACE ASPHALT CEMENT CONCRETE RECYCLING (NEW) Section 2318

April 20, 2004
Supersedes October 3, 2000

MATERIAL OR CONSTRUCTION ITEM	TESTS	METHOD OF ACCEPTANCE & RELATED IMs	QC/ACCEPTANCE S&T					ASSURANCE, CORRELATION AND VERIFICATION S&T						REMARKS ➡➡
			SAMPLE BY	FREQ.	SAMPLE SIZE	TEST BY	REPORT	S&T TYPE	SAMPLE BY	FREQ.	SAMPLE SIZE	TEST BY	REPORT	
SOURCE INSPECTION														
Emulsion (Rej. Agent) (2318.02)	Quality	AS 437												
GRADE INSPECTION														
RAP (2318.02)	Max Size		RCE	1 st day + 1/ week	5 kg	RCE								
Emulsion (Rej. Agent)	Quality Residue	Cert D 360	RCE	1/day	1 L ➡➡	DME								Must use plastic bottle
Uncompacted Mixture (2318.04)	Moisture Density	504 504	RCE RCE	1/lot 1/lot	14 kg ➡➡ 14 kg	DME DME								Sealed Container
Compacted Mixture (2318.04)	Moisture* Density	504 504	CONTR CONTR	7/day 7/day		CONTR CONTR➡➡								Witnessed by RCE
AS-Approved Source AB-Approved Brand ASD-Approved Shop Drawing S&T-Sampling & Testing		Cert A-Type A Certification Cert C-Type C Certification Cert D-Type D Certification			RCE-Resident Construction Engineer/Project Engineer DME-District Materials Engineer CTRL-Central Materials Office CONTR-Contractor				ASSUR-Independent Assurance VERIF-Verification CORR-Correlation MON-Monitor					

*See IM 504 for Day 1 moisture correction factor.